

⁽¹²⁾ UK Patent Application ⁽¹⁹⁾ GB ⁽¹¹⁾ 2 076 535 A

- (21) Application No **8106626**
- (22) Date of filing **3 Mar 1981**
- (30) Priority data
- (31) **144135**
- (32) **28 Apr 1980**
- (33) **United States of America
(US)**
- (43) Application published
2 Dec 1981
- (51) INT CL³
G01K 1/14 G01L 19/00
- (52) Domestic classification
**G1D 52
G1L 3L**
- (56) Documents cited
None
- (58) Field of search
**G1D
G1L
H1K**
- (71) Applicant
**General Electric
Company,
1, River Road,
Schenectady, 12305,
State of New York, United
States of America**
- (72) Inventors
**Nicholas Edward Hollis,
Michael Paul Swift,
Herbert Halila**
- (74) Agent
**Brookes & Martin,
High Holborn House, 52—
54, High Holborn, London,
WC1V 6SE**

(54) Removable Probe-carrying Sealing Plug for Spaced Apart Wall Structure

(57) The plug includes an axial shaft 12, a mating end 18 of which is spring coupled to a mating portion 26 of a sealing plug 20. The other end of the shaft includes an externally threaded portion 14 and a flanged portion 16. The sealing plug also includes an externally threaded portion 22 and a flanged portion 24. The spring normally mates the shaft and sealing plug together so that the members are

rotationally engaged and portion 14 can be engaged with threading 1A in wall 1. When the spring is suitably compressed, Fig. 2 (not shown), the mating relationship is removed so that the members are rotationally disengaged and portion 22 can be engaged with threading 2A in wall 2. The plug is particularly useful in conveniently sealing double wall combustors such as those in gas turbine engines whilst carrying a probe 40 to measure, e.g. temperature and pressure, between walls 1 and 2 and to the side of wall 1 remote from wall 2.




Fig 7

[illegible]

GB 2 076 535 A

1 / 1




Fig 1




Fig 2

SPECIFICATION

Removable Sealing Plug for Spaced Apart Wall Structure

The present invention relates to aperture sealing means and, more particularly, to such sealing means for sealing opposing apertures in a structure of the type having spaced apart walls.

In carrying out one form of our invention, we provide apparatus for removably sealing at least a pair of opposing apertures in a structure of the type having at least two spaced apart walls. Each of the walls includes at least one of the opposing apertures. First shaft means is provided and extends between the two spaced apart walls. The first shaft means includes a pair of axially opposing ends. One of the ends includes fastening and sealing means for removably fastening in a substantially sealed manner to the opposing aperture in one of the walls. The other of the ends includes first mating means for mating with a second sealing means. Rotationally torqueable second sealing means is provided and includes fastening and sealing means for removably fastening in a substantially sealed manner to the opposing aperture in the other wall. The second sealing means further includes second mating means for mating with the first mating means. Compressible spring means couples the first shaft means and the second sealing means for engaging the first and second mating means wherein the first and second mating means are normally urged together by the spring means and wherein the first shaft means and the second sealing means are rotationally engaged such that rotational torque applied to the second sealing means is transferred to the first sealing means. A predetermined compression of the spring means separates the first and second mating means such that the first shaft means and the second sealing means are rotationally disengaged.

Figure 1 is a partially sectioned elevational view showing one form of removable sealing means of the present invention.

Figure 2 is a partially sectioned elevational view, taken as in Figure 1, showing one form of operation of the removable sealing means of Figure 1.

Referring initially to Figure 1, one form of sealing means of the present invention is generally designated 10 and, may, for example, represent a borescope plug. The borescope plug 10 includes a first axial shaft 12 having a pair of opposing axial ends 12A and 12B. The end 12A of the shaft 12 includes fastening means 14 which may, for example, be in the form of conventional external threads. The end 12A also includes sealing means 16 which may, for example, be in the form of a flange, for sealing internally threaded aperture 1A in wall 1. For reasons which will be more fully understood later, the end 12A may also include a wrenching portion 19. The other end 12B of the shaft 12

example, comprise a hexagonally shaped structure.

Second sealing means 20 which may, for example, be in the form of a rotationally torqueable plug, is provided for mating with first shaft 12. Plug 20 includes fastening means 22, which may, for example, be in the form of conventional external threads for fastening to an internally threaded aperture 2A in wall 2. Plug 20 also includes sealing means 24, which may be in the form of a flange, for sealing to wall 2. Plug 20 includes mating means 26 for mating with mating means 18 of shaft 12. More particularly, mating means 26 may be in the form of an internally formed, i.e. female, hexagonal structure for mating with the corresponding externally formed, i.e., male, hexagonal mating means 18. For reasons which will be more fully understood later, the internal mating means 26 of plug 20 extends axially only for a distance D within the plug 20. Also, a clearance C is provided between the mating means 18 and the axial inner sidewall 20S of the plug 20 (see Figure 2). A ring 28, preferably removable, is provided in groove 28' to restrain axial movement of mating means 18 completely out of plug 20.

Compressible spring means 30 is provided for coupling shaft mating means 18 with plug mating means 26. The compressible spring means 30 may be positioned between axially outer surface 18A of mating means 18 and axially inner surface 20A of plug 20. The normal position of the plug 20 is as shown in Figure 1. More particularly, in the normal position, spring 30 urges shaft mating means 18 and plug mating means 26 together. In this position, the shaft 12 and plug 20 are rotationally engaged such that rotational torque applied to the plug 20 is transferred to the shaft 12.

Referring now to the operation of the borescope plug 10. Typically, beginning with the normal position of Figure 1 for a sealing operation, rotational torque (see arrow R) is applied to the relatively large torqueable wrenching head 32 of the outer plug 20. The head 32 is sized so as to be capable of transferring the desired magnitude of rotational torque. This rotational torque is transferred to the shaft 12 and, hence, to the fastening means 14. The head 32 is continued to be torqued so as to sufficiently fasten and seal the aperture 1A in wall 1. When shaft 12 and flange 16 have sufficiently sealed the aperture 1A in wall 1, the spring 30 is then compressed, wherein mating means 18 and 26 are no longer mated and plug 20 and shaft 12 are rotationally disengaged. This position of rotational disengagement is shown in Figure 2 wherein like reference numerals represent like elements of Figure 1. Accordingly, at this position, head 32 of plug 20 can be further rotationally torqued until fastening means 22 securely fastens and sealing means 24 appropriately seals the aperture 2A in wall 2, resulting in the relationship shown in Figure 2.

10, when in the sealed position of Figure 2, permits axial and transverse relative movement of the plug 20 and shaft 12 (see arrows). This relative movement is particularly desirable for applications involving environments characterized by thermal variations and/or mechanical deflections.

Removal of the plug 10 from the opposing apertures in the spaced apart walls 1 and 2 is simply accomplished by reversing the above procedures. More particularly, beginning with the position shown in Figure 2, plug 20 is simply reverse rotated until the aperture 2A in the wall 2 is no longer sealed and the spring 30 is no longer compressed. At this point, the relationship shown in Figure 1 is obtained such that the mating means 18 and 26 are again mated and further reverse rotation of head 32 of plug 20 will remove end 12A from its fastening and sealing relationship to aperture 1A in wall 1.

It is to be appreciated that, if desired, the borescope 10 of Figure 1 could also serve as an inspection and/or monitoring device. In this connection, as partially shown in Figure 2, the borescope plug 10 may actually include, or comprise, probe means 40 for observing properties, such as temperature and pressure, within the space defined between walls 1 and 2, as well as in the space beyond wall 1.

30 Claims

1. Apparatus for removably sealing at least a pair of opposing apertures in a structure of the type having at least two spaced apart walls wherein each of the walls includes at least one of the opposing apertures, which comprises:

(a) first shaft means for extending between the two spaced apart walls and having a pair of axially opposing ends, one of said ends including fastening and sealing means for removably fastening in a substantially sealed manner to the opposing aperture in one of the walls, the other of said ends including first mating means for mating with a second sealing means;

(b) rotationally torqueable second sealing means including fastening and sealing means for removably fastening in a substantially sealed manner to the opposing aperture in the other wall and further including second mating means for mating with said first mating means; and

(c) compressible spring means coupling said first shaft means and said second sealing means for engaging said first and second mating means wherein:

(i) said first and second mating means are normally urged together by said spring means and wherein said first shaft means and second sealing means are rotationally engaged such that rotational torque applied to said second sealing means is transferred to said first sealing means; and

(ii) a predetermined compression of said spring means separates said first and second mating means such that said first shaft means and said second sealing means are rotationally disengaged.

2. Apparatus in accordance with claim 1 which comprises a borescope plug.

3. Apparatus in accordance with claim 2 in which said borescope plug includes probe means for observing properties within the space defined between the two spaced walls.

4. Apparatus in accordance with claim 2 in which said borescope plug includes probe means for observing properties in the space beyond the one wall and remote from the other wall.

5. Apparatus in accordance with claim 2 in which said second sealing means includes a rotationally torqueable plug and in which said fastening means of said second sealing means includes external threads.

6. Apparatus in accordance with claim 5 in which said sealing means of said second sealing means includes a flange.

7. Apparatus in accordance with claim 2 in which said fastening means of said first sealing means includes external threads.

8. Apparatus in accordance with claim 7 in which said sealing means of said first sealing means includes a flange.

9. Apparatus in accordance with claim 2 in which said first mating means comprises a male member and said second mating means comprises a corresponding female member.

10. Apparatus in accordance with claim 8 in which said second mating means extends only partially axially into said second sealing means.

11. Apparatus in accordance with claim 2 in which the spaced apart walls comprise compressor walls in a gas turbine engine.

12. Apparatus in accordance with claim 2 in which the spaced apart walls comprise combustor walls in a gas turbine engine.

13. Apparatus for removably sealing at least a pair of apertures substantially as hereinbefore described with reference to and as illustrated in the drawings.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.